



CXVE 0806-0818

Refrigerant condensers

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

Last update: 01/07/2024

CXVE 0806-0818



1. Refrigerant in; 2. Refrigerant out; 3. Make up; 4. Overflow; 5. Drain; 6. Access door.



Model	Weights (kg)			Dimensions (mm)			Air Flow (m ³ /s)	Fan Motor (kW)	Water Flow (l/s)	Pump Motor (kW)	R717 charge (kg)
	Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H					
CXVE 111-08 06-10L	3960	2820	1680	1822	2584	4792	16.1	(1x) 7.5	18.3	(1x) 1.5	40.0
CXVE 151-08 09-10L	5420	3680	2140	2737	2584	4792	20.7	(2x) 4.0	34.7	(1x) 4.0	48.0
CXVE 176-08 09-20L	5710	3950	2420	2737	2584	4792	25.2	(2x) 7.5	34.7	(1x) 4.0	60.0
CXVE 190-08 09-15L	6360	4580	3200	2737	2584	5673	22.8	(2x) 5.5	34.7	(1x) 4.0	85.0
CXVE 207-08 09-20L	6790	4990	3610	2737	2584	5673	24.6	(2x) 7.5	34.7	(1x) 4.0	109.0
CXVE 217-08 12-15L	7170	4810	2980	3651	2584	4792	29.7	(2x) 5.5	45.4	(1x) 4.0	81.0
CXVE 227-08 12-20L	7200	4840	3010	3651	2584	4792	32.3	(2x) 7.5	45.4	(1x) 4.0	81.0
CXVE 239-08 12-30L	7250	4890	3060	3651	2584	4792	35.7	(2x) 11.0	45.4	(1x) 4.0	81.0
CXVE 259-08 12-20L	7980	5580	3960	3651	2584	5673	31.8	(2x) 7.5	45.4	(1x) 4.0	114.0
CXVE 264-08 12-30L	7750	5380	3750	3651	2584	5673	35.5	(2x) 11.0	45.4	(1x) 4.0	97.0
CXVE 279-08 12-30L	8290	5880	4260	3651	2584	5673	36.6	(2x) 11.0	45.4	(1x) 4.0	130.0
CXVE 284-08 12-30L	8550	6120	4500	3651	2584	5673	36.5	(2x) 11.0	45.4	(1x) 4.0	146.0
CXVE 298-08 18-22.5 L	10580	7000	4270	5480	2584	4945	42.7	(3x) 5.5	54.6	(1x) 5.5	122.0
CXVE 310-08 18-30L	10610	7030	4310	5480	2584	4945	50.0	(3x) 7.5	54.6	(1x) 5.5	122.0
CXVE 329-08 18-22.5 L	11390	7780	5340	5480	2584	5826	42.4	(3x) 5.5	54.6	(1x) 5.5	146.0
CXVE 345-08 18-30L	11420	7810	5380	5480	2584	5826	49.6	(3x) 7.5	54.6	(1x) 5.5	146.0
CXVE 373-08 18-30L	12140	8500	6060	5480	2584	5826	51.6	(3x) 7.5	54.6	(1x) 5.5	183.0
CXVE 387-08	12720	9040	6600	5480	2584	5826	48.6	(3x) 7.5	54.6	(1x) 5.5	219.0



18-30L											
CXVE 395-08 18-45L	12250	8610	6170	5480	2584	5826	59.6	(3x) 11.0	54.6	(1x) 5.5	183.0
CXVE 409-08 18-45L	12810	9130	6700	5480	2584	5826	55.6	(3x) 11.0	54.6	(1x) 5.5	219.0